



- Fresh Air Intake
- Silent
- Auto Restart Function
- Self-diagnosis Function
- Sleep Mode

Jet-Air
Cool, Warm & Collected
Ducted Split

R410A



Proudly distributed by

JASA
Smart Home



Ducted Split Type Technical Specifications



- Fresh Air Intake
- Self-diagnosis Function
- Auto Restart Function
- Silent
- Sleep Mode

Model	Indoor		JASA-HI-H24A4/R	JASA-HI-H36A4/R	JASA-HI-H36A5/R	JASA-HI-H48A5/R	JASA-HI-H60A5/R
	Outdoor		JASA-H24A4/R	JASA-H36A4/R	JASA-H36A5/R	JASA-H48A5/R	JASA-H60A5/R
Power Supply	V~, Hz, Ph		220~240, 50, 1	220~240, 50, 1	380~415, 50, 3	380~415, 50, 3	380~415, 50, 3
Capacity	Cooling	Btu/h	24000	36000	36000	48000	60000
		kw	7.03	10.60	10.60	14.00	17.60
	Heating	Btu/h	26900	39920	39920	52000	63500
		kw	7.88	11.70	11.70	15.24	18.50
Electric Data	Rated Cooling Power Input	kw	2.26	3.77	3.73	4.90	6.26
	Rated Heating Power Input	kw	2.18	3.50	3.50	5.05	5.78
	Rated Cooling Current	A	10.37	17.30	6.69	8.88	11.34
	Rated Heating Current	A	10.00	16.60	6.28	9.33	10.36
Performance	EER/COP	w/w	3.11/3.61	2.81/3.34	2.84/3.34	2.87/3.02	2.81/3.20
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1400/1250/1050	2000/1600/1400	2000/1600/1400	2400/2100/1700	2600/2300/1950
	Noise Level (Hi/Mi/Lo)	dB(A)	46/44/42	50/47/41	50/47/41	49/46/44	50/47/45
	External Static Pressure	Pa	80	80	80	80	80
	Net Dimension (W*H*D)	mm	890*735*290	890*735*290	890*735*290	1250*735*290	1250*735*290
	Packing Dimension (W*H*D)	mm	1070*800*360	1070*800*360	1070*800*360	1430*800*360	1430*800*360
	Net/Gross Weight	kg	33/38	35/39	35/39	45/51	50/56
Outdoor Unit	Noise Level	dB(A)	57	60	60	60	60
	Dimension (W*D*H)	mm	825*310*655	970*395*805	970*395*805	940*340*1325	940*340*1325
	Packing	mm	945*435*725	1105*495*895	1105*495*895	1070*450*1435	1070*450*1435
	Weight	kg	53/56	65/75	65/75	95/105	99/109
Refrigerant Pipe	Liquid Side	inch	3/8"	3/8"	3/8"	3/8"	3/8"
	Gas Side	inch	5/8"	5/8"	5/8"	3/4"	3/4"
	Max. Length	m	20	30	30	50	50
	Max. Height	m	15	20	20	30	30



12-24K



36K



48-60K

